

ATH W®44 P

Obrázky produktu



- **Pneumatic shaft:** 40 mm clamping shaft for quick and secure wheel clamping
- **Sonar technology:** Non-contact rim width detection
- **Automatic positioning:** Automatically positions the wheel for weight attachment
- **Extended clamping shaft:** Additional clamping shaft for use with other clamping devices
- **Laser indicator:** Enables precise placement of the clamping weights at the 5 o'clock position
- **Static/Dynamic program:** Enables optimal balancing at different speeds
- **Alu balancing programs:** Special programs for aluminum rims to improve balancing quality
- **Split rear spoke weight positioning:** Enables precise weight distribution behind the spokes
- **Optimization program:** Program for fine-tuning and optimizing the balancing process
- **Optional motorcycle function:** Additional function for balancing motorcycle wheels

Další informace

Průměr centrálního vývrtu	45 – 130 mm
Messzeit PKW LKW	8 s
Tolerance měření	+/- 1g
Rychlost měření	200 U/min
Šířka ráfku	1,5" – 20"
Průměr ráfku	10" – 24"
Šířka kola max.	900 mm
Max. hmotnost kola	65 kg
Připojení stlačeného vzduchu	6 bar
Monitor	22" LED
Příkon	0,20 kW
Napájení	230V / C16A

